

Declaration of Performance

No. DOP_LE8P02_12209

1. Identification code of product type

Mortise lock series LE8P including the models: LE8P12xx, LE8P22xx

2. Name and address of the manufacturer

Salto Systems S.L. (c/Arkotz, 9 - 20180 Oiartzun – Spain - CIF B20708517)

3. Intended use of the construction product

Mortise lock for fire doors

4. System of assessment and verification of constancy of performance: System 1

5. Notified body 1239 TECNALIA R&I Certificación, S.L. performed initial tests, initial manufacturing plant inspection and surveillance, assessment and continuous approval of factory production center, under System 1 and issued the conformity certificate 1239/CPR/0802902:

6. Declared performance

Essential characteristics*	Performance		Harmonised technical specification
*Category of use	3	High frequency of use and misuse	EN 12209: 2003 +/AC : 2005
*Durability and load on latch bolt	M	200.000 cycles and y 25N on latch	
*Door mass and closing force	2	≤200 kg F closing ≤50N	
*Suitability for use on fire/smoke doors	1	Suitable for use on fire/smoke resisting doors	
Safety	0	No safety requirement	
Corrosion resistance and temperature	F	High corrosion resistance, from -20°C to 80°C	
Security and drill resistance	2	Low security and without drilling resistance	
Field of door application	B	Mortise lock for hinged door	
Type of key operation and locking	C	Lock with cylinder. Manual blocking with intermediate blocking	
Type of spindle operation	1	Lever with spring	
Key identification	0	No requirements	

7. The performance of the product identified in point 1, is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2.



Oiartzun, 2013/07/01

Juan Imedio
R&D Director