Datasheet

Next-generation technology and smart innovations for a more connected, keyless building experience.





SALTO Keyfobs CFAD2xx

Technical specifications:

Built in ABS, waterproof housing, these keyfob are equipped with the NXP MIFARE DESFire Common Criteria EAL5+ security-certified chip, offering the best in the market alternative for RFID-based physical key products.

Publications of SALTO SYSTEMS S.L. are protected by copyright and all rights are reserved. SALTO SYSTEMS publications may not be reproduced in any form or by any means without written permission from the copyright owner.

saltosystems .com



TECHNICAL DATA:

Keyfob size :	34mm x 41,4mm
Material:	ABS body
Chip manufacturer:	NXP Semiconductors
Chip type:	MIFARE® DESFire®1

¹ Please contact SALTO inside sales for information on the latest family evolution available

SALTO PLATFORM COMPATIBILITY:

Version / Model	5
D207	•

COLORS:

Available in white, SALTO design with different colors, or with customerspecific artwork options based on specific customer needs.

Blue	•
Red	•
Green	•
Yellow	•
Black	•

RFID MAIN FEATURES:

RF interface: ISO/IEC 14443 Type A

- Contactless interface compliant with ISO/IEC 14443-2/3 A
- Operating frequency: 13.56 MHz
- Fast data transfer: 106 kbit/s, 212 kbit/s, 424 kbit/s, 848 kbit/s
- 7 bytes unique identifier
- Uses ISO/IEC 14443-4 transmission protocol

Non-volatile memory

- 2 KB (D207)
- Data retention of 25 years
- Write endurance typical 1,000,000 cycles
- Fast programming cycle

NV-memory organization and multi-application support

The DESFire PICC-level configuration allows creation of 3rd Party Application without presenting PMK, provided that the intended application fits in the free memory available.

Security

- Common Criteria certification: EAL5+ (Hardware and Software)
- Unique 7 bytes serial number for each device
- Mutual three-pass authentication
- Hardware AES using 128-bit keys featuring key version
- Data authenticity by 8 byte CMAC
 - MF3ICD40 compatible mode: 4 byte MAC, CRC 16
- Data encryption on RF-channel
- Authentication on application level
- Hardware exception sensors
- Self-securing file system
- Originality Check for proof of genuine NXP's product

Special features

Transaction-oriented automatic anti-tear mechanism with new transaction timer support.



SALTO Systems.

Get in touch with our team.

Give us a brief summary of your needs, your next project and we'll get back to you.

Spain, UK, France, Germany, Switzerland, The Netherlands, Belgium, Poland, Slovakia, Slovenia, Czech Republic, Denmark, Norway, Sweden, Finland, Italy, Portugal, US (NYC - Atlanta - LV), Canada, Mexico, Costa Rica, Colombia, Puerto Rico, Chile, UAE, India, South Africa, Singapore, China, Hong Kong, Korea, Vietnam, Australia, New Zealand.

saltosystems .com

Copyright © 2024 SALTO Systems